

Cutler-Hammer

Cutler-Hammer
Five Parkway Center
Pittsburgh, Pennsylvania, U.S.A. 15220

Application Data
29-167G

Page 1

April 1998

Time/Current Characteristic Curves for
Series C® G-Frame Circuit Breakers

AB DE-ION® Circuit Breakers

Voltages shown in curve headings are maximum at which the breaker may be applied. Interrupting capacity of individual breaker is tabulated on each curve.

Breaker Description	Curve No.	Page
Types GB, GHB, GC, GHC 15-100 Amperes, 1 Pole	SC-3500-83B	2
Types GB, GHB, GC, GHC 15-100 Amperes, 2, 3 Poles	SC-3501-83B	3
Type GD 15-100 Amperes, 2, 3 Poles	SC-6030-95	4
Types GHBGFEP, GHCGFEP 15-60 Amperes, 2 Pole	SC-6759-97	5
Types GHBS and GBHS 15-30 Amperes, 1, 2 Poles	SC-5695-93B	6


Individual oversize copies of curves listed above printed on onion-skin paper are available in limited quantity from:

Cutler-Hammer
Five Parkway Center
Pittsburgh, PA 15220

When ordering onion-skin curves, use number at bottom of page where curve appears, i.e., SC-3500-83B. **Requests for full sets of curves will not be honored.**




AB DE-ION Circuit Breakers
Types GB, GHB, GC, GHC 15-100 Amperes, 1 Pole





AB DE-ION Circuit Breakers


Types GB, GHB, GC, GHC 15-100 Amperes, 2 and 3 Poles



Curve No. SC-3501-83B




AB DE-ION Circuit Breakers
Type GD 15-100 Amperes, 2 and 3 Poles






AB DE-ION Circuit Breakers

Types GHBGFEP, GHCGFEP 15-60 Amperes, 2 Pole (Single Phase)



Type GHBS 15-30 Amperes, 1, 2 Poles



Curve No. SC 5695-93B